




GPS Track USA

FL4 GPS Tracking Device

10600 W. Mitchell Street, West Allis, WI 53214



Standard OBDII Port



INSTALLATION

Finding the OBDII Port:

- Most vehicle's OBDII ports are typically located near the base of the steering column, on either side of the center console, or in the driver's side kick-panel
- Note that some vehicles and installation types require an extension or an adaptor harness for secure installation and proper operation

Installing the Device – Standard Installation

- With the ignition off, align the socket-end of the FL4 with the vehicle's OBDII port and push into place
- Be sure the FL4 is securely connected to the vehicle's OBDII port
- When the FL4 has been properly connected, you should hear a number of quick beeps and see all three LEDs flash briefly

Installation Validation:

- Cycle the vehicle's ignition on and back off
- Log in to the user interface
- Find the device in the vehicle list
- Check for ignition on and ignition off events

LED Diagram:



O – OBD C – Cell G – GPS

LED	Color	Status	LED Description
O - OBD	Orange	Ignition OFF	Off
		Ignition ON	Blinking
C - Cell	Blue	Searching for Network	Off
		Network Lock	Blinking
G - GPS	Green	Searching for GPS	Solid
		GPS Lock	Blinking

CAUTION:

If the angle of the vehicle's OBDII port positions the device in a place where it could easily get kicked or otherwise knocked out of place, order the available accessory extension cable and use it to reposition the device into a more secure location

QUICK TIP:

If the device fails to validate, check:

- Cellular coverage in the area
- That the device is connected securely
- Whether there are any obstructions from above that might interfere with GPS reception

If you have any questions regarding your device, please call: 262-308-4471 or email: info@gpstrackusa.com